COMPUTER SUBROUTINES FOR THE ESTIMATION OF NUCLEAR REACTION EFFECTS IN PROTON-TISSUE-DOSE CALCULATIONS

John W. Wilson and G. S. Khandelwal

Langley Research Center
Hampton, Va. 23665

1. Report No. NASA TM X-3388	2. Government Accession No.	3. Recipient's Catalog No.
4. Title and Subtitle COMPUTER SUBROUTINES FOR THE ESTIMATION OF NUCLEAR REACTION EFFECTS IN PROTON-TISSUE-DOSE CALCULATIONS		5. Report Date June 1976
		6. Performing Organization Code
7. Author(s) John W. Wilson and G. S. Khandelwal		8. Performing Organization Report No. L-10824
9. Performing Organization Name and Address NASA Langley Research Center Hampton, Va. 23665		10. Work Unit No. 506-16-37-01
		11. Contract or Grant No.
12. Sponsoring Agency Name and Address National Aeronautics and Space Administration Washington, D.C. 20546		13. Type of Report and Period Covered Technical Memorandum
		14. Sponsoring Agency Code

15. Supplementary Notes

G. S. Khandelwal: Professor of Physics, Old Dominion University, Norfolk, Va.

16. Abstract

Calculational methods for estimation of dose from external proton exposure of arbitrary convex bodies are briefly reviewed and all the necessary information for the estimation of dose in soft tissue is presented. Special emphasis is placed on retaining the effects of nuclear reaction, especially in relation to the dose equivalent. Computer subroutines to evaluate all of the relevant functions are discussed. Nuclear reaction contributions for standard space radiations are in most cases found to be significant. Many of the existing computer programs for estimating dose in which nuclear reaction effects are neglected can be readily converted to include nuclear reaction effects by use of the subroutines described herein.

17. Key Words (Suggested by Author(s)) Radiation Doses Nuclear reaction	18. Distribution Statement Unclassified – Unlimited Subject Category 93
19. Security Classif. (of this report) Unclassified	20. Security Classif. (of this page) Unclassified	21. No. of Pages 24	22. Price* $3.25

COMPUTER SUBROUTINES FOR THE ESTIMATION OF NUCLEAR REACTION
EFFECTS IN PROTON-TISSUE-DOSE CALCULATIONS

John W. Wilson and G. S. Khandelwal*
Langley Research Center

SUMMARY

Calculational methods for estimation of dose from external proton exposure of arbi-
trary convex bodies are briefly reviewed and all the necessary information for the estima-
tion of dose in soft tissue is presented. Special emphasis is placed on retaining the effects
of nuclear reaction, especially in relation to the dose equivalent. Computer subroutines
to evaluate all of the relevant functions are discussed. Nuclear reaction contributions for
standard space radiations are in most cases found to be significant. Many of the existing
computer programs for estimating dose in which nuclear reaction effects are neglected
can be readily converted to include nuclear reaction effects by use of the subroutines
described herein.

INTRODUCTION

When an object is exposed to external radiation, the dose field within the object is
a complicated function of the character of the external radiation, the shape of the object
(including orientation), and the object's material composition. Calculation of dose within
an object involves solution of the appropriate Boltzmann transport equation in which the
external radiation source imposes boundary conditions on the solution. Although general
purpose computer programs exist for making such estimates (ref. 1), they are seldom
used in practice when the object is bounded by a complicated surface, as is the human
body, for example. Instead, calculations are usually made for simple geometric shapes
from which inferences are then made for more general geometries, and the resultant
errors are uncertain.

In the case of external proton radiation, such as that encountered near high-energy
accelerators, in space, and in high-altitude aircraft, it is the inclusion of nuclear reaction
effects which presents the major hurdles in an accurate calculation. It was found in ref-
erence 2 that dose estimation could be greatly simplified and still include the effects of
nuclear reaction. Furthermore, it was shown that the method of reference 2, when in
error, was always conservative. Required for such calculations is a knowledge of the

―――――――――――――――――――――――――――
*Professor of Physics, Old Dominion University, Norfolk, Va.

transition of protons in semi-infinite slab geometry, which is the simplest geometry for existing transport computer programs. Indeed, almost everything that is known about the dose in humans from external proton radiation is inferred from calculations with slab geometry (ref. 3).

In the present report, a general method for estimation of dose in arbitrary convex geometry in terms of dose conversion factors in slab geometry is briefly discussed. These dose conversion factors for protons in tissue are then represented using buildup factors. A parametric form for the buildup factors is presented. The values for the parameters are derived from Monte Carlo calculations of various authors. All the information necessary to estimate dose and dose equivalent for proton irradiation of convex objects of arbitrary shape is contained herein. The advantage of the method is that existing proton dose calculations in which nuclear reactions are neglected can be directly converted by substitution of the dose conversion factors presented herein.

SYMBOLS

a_i buildup-factor parameter, $i = 1, 2, 3, 4$

$D(\vec{x})$ dose at point $\vec{x}$, rad or rem

E proton energy, MeV

E_o proton energy parameter, MeV

E_r reduced proton energy, MeV

$F(z,E)$ proton dose buildup factor, dimensionless

$P(E)$ nuclear survival probability in tissue

$p(E)$ particle rigidity, MV/c

p_o particle rigidity parameter, MV/c

$Q_F(S)$ quality factor, dimensionless

$r(E)$ proton range in tissue

$R_n(z,E)$ dose conversion factor for normal incident protons, $\dfrac{\text{rad (or rem) cm}^2}{\text{proton}}$

$R_p(z,E)$ primary proton contribution to $R_n(z,E)$, $\dfrac{\text{rad (or rem) cm}^2}{\text{proton}}$

$R_s(z,E)$ secondary particle contribution to $R_n(z,E)$, $\dfrac{\text{rad (or rem) cm}^2}{\text{proton}}$

$S(E)$ proton energy loss rate in tissue, MeV/cm

$\vec{x}$ dose point position vector, cm

z depth of penetration into a tissue slab, cm

$z_x(\vec{\Omega})$ distance from surface to dose point $\vec{x}$ along direction $\vec{\Omega}$, cm

$\epsilon(z)$ energy of proton with range z in tissue, MeV

$\sigma(E)$ proton macroscopic cross section in tissue, cm^{-1}

$\tau(E)$ proton total optical thickness, dimensionless

$\phi(\vec{\Omega},E)$ proton differential fluence spectrum, protons/cm^2-MeV-sr

ϕ_0 proton differential fluence spectrum parameter, protons/cm^2-MeV-sr

$\vec{\Omega}$ unit vector in direction of proton motion, dimensionless

Abbreviations:

GCR   galactic cosmic radiation

SCR   solar cosmic radiation

A prime indicates a variable of integration.

THEORY

In passing through tissue, energetic protons interact mostly through ionization of atomic constituents by the transfer of small amounts of momentum to orbital electrons. Although the nuclear reactions are far less numerous, their effects are magnified because of the large momentum transferred to the nuclear particles and to the struck nucleus itself. Unlike the secondary electrons formed through atomic ionization by interaction with the primary protons, the resulting radiations of nuclear reaction are nearly all heavily ionizing and generally have large biological effectiveness. Many of the secondary particles of nuclear reactions are sufficiently energetic to promote similar nuclear reactions and thus cause a buildup of secondary radiations. The description of such processes requires solution of the transport equation. The approximate solution for the transition of protons in 30-cm-thick slabs of soft tissue for fixed incident energies are presented in references 4 to 11. The results of such calculations are dose conversion factors for relating the primary monoenergetic proton fluence to dose or dose equivalent as a function of position in a tissue slab.

Whenever the radiation is spatially uniform, the dose at any point $\vec{x}$ in a convex object may be calculated according to reference 2 by

$$D(\vec{x}) = \int_0^\infty \int_\Omega R_n\left[z_x(\vec{\Omega}),E\right] \phi(\vec{\Omega},E) \, d\vec{\Omega} \, dE \tag{1}$$

where $R_n(z,E)$ is the dose at depth z for normal incident protons of energy E on a tissue slab, $\phi(\vec{\Omega},E)$ is a differential proton fluence along direction $\vec{\Omega}$, and $z_x(\vec{\Omega})$ is the distance from the boundary along $\vec{\Omega}$ to the point $\vec{x}$. It has been shown that equation (1) always overestimates the dose but gives an accurate estimate when the ratio of the proton beam divergence due to nuclear reaction to the body radius of curvature is small. Equation (1) is a practical prescription for introducing nuclear reaction effects into calculations of dose in geometrically complex objects such as the human body. The main requirement is that the dose conversion factors for a tissue slab be adequately known for a broad range of energies and depths.

Available information on conversion factors is for discrete energies from 100 MeV to 1 TeV in rather broad energy steps and for depths from 0 to 30 cm in semi-infinite slabs of tissue (refs. 4, 5, 8, and 9). The nuclear reaction data used for high-energy nucleons are usually based on Monte Carlo estimates (refs. 12 to 14) with low-energy neutron reaction data taken from experimental observation. The quality factor defined by the International Commission on Radiobiological Protection (ref. 15) is used for protons. The quality factor for heavier fragments and the recoiling nuclei is arbitrarily set to 20, which

is considered conservative, although the average quality factor obtained by calculation is comparable to estimates obtained through observations made in nuclear emulsion (ref. 16).

To fully utilize equation (1), the fluence-to-dose conversion factors for normal incident protons on a tissue slab must be known for all energies and depths. A parametrization of the conversion factors was introduced by Wilson and Khandelwal (ref. 2) which allowed reliable interpolation and extrapolation from known values. In the following section, a refinement and extension of that work will be discussed.

Fluence-to-Dose Conversion Factors

The conversion factor $R_n(z,E)$ is composed of two terms representing dose due to the primary beam protons and the dose due to secondary particles produced in nuclear reaction. Thus,

$$R_n(z,E) = R_p(z,E) + R_s(z,E) \tag{2}$$

where the primary dose equivalent conversion factor is given by

$$R_p(z,E) = P(E) \, Q_F\left[S(E_r)\right] \frac{S(E_r)}{P(E_r)} \tag{3}$$

The linear energy transfer (LET) denoted by $S(E)$ in equation (3) is calculated by using Bethe's formula above 243.8 keV as given by

$$S(E) = \frac{4\pi N_A e^4 z}{m_e v^2 A} \left\{ \ln\left[\frac{2m_e v^2}{I\left(1 - \frac{v^2}{c^2}\right)}\right] - \frac{v^2}{c^2} \right\} \tag{4a}$$

where

z   average tissue atomic number

A   average tissue atomic weight

I   adjusted ionization potential

m_e electron mass

e   electron charge, C

v   proton velocity, cm/sec

c   velocity of light, cm/sec

N_A Avogadro's number

At proton energies below 243.8 keV, the LET is calculated by the empirical expression

$$S(E) = E^{0.303}(2517 - 6283E) \tag{4b}$$

which approximately accounts for electron capture and the inner shell corrections in soft tissue. The proton range in soft tissue is given by

$$r(E) = \int_0^E \frac{dE'}{S(E')} \tag{5}$$

with the reduced energy in equation (3) given by

$$E_r = \epsilon\left[r(E) - z\right] \tag{6}$$

where $\epsilon(z)$ is the inverse function of $r(E)$. The total nuclear survival probability for a proton of energy E is given by

$$P(E) = \exp\left[-\int_0^E \sigma(E') \frac{dE'}{S(E')}\right] \tag{7}$$

where the macroscopic cross section $\sigma(E)$ for tissue as calculated by Bertini is given in reference 17. The proton total optical thickness given by

$$\tau(E) = \int_0^E \sigma(E') \frac{dE'}{S(E')} \tag{8}$$

is tabulated in table 1 for purposes of numerical interpolation. In the case of conversion factors for absorbed dose, $R_p(z,E)$ is taken as

$$R_p(z,E) = P(E) \frac{S(E_r)}{P(E_r)} \tag{9}$$

6

Buildup Factors

The representation of the conversion factors is simplified (see ref. 2) by rewriting equation (2) as

$$R_n(z,E) = \left[1 + \frac{R_s(z,E)}{R_p(z,E)}\right] R_p(z,E)$$

or

$$R_n(z,E) \equiv F(z,E)\, R_p(z,E) \tag{10}$$

where $F(z,E)$ is recognized as the proton dose buildup factor. The main advantage for introducing the buildup factor into equation (10) is that unlike $R_n(z,E)$, the buildup factor is a smoothly varying function of energy at all depths in the slab and can be approximated by the simple function

$$F(z,E) = \left(a_1 + a_2 z + a_3 z^2\right) \exp\left(-a_4 z\right) \tag{11}$$

where the parameters a_i are energy dependent. The a_i coefficients are found by fitting equation (11) to the values of the buildup factors as estimated from the Monte Carlo calculations of proton conversion factors. The resulting coefficients are shown in table 2. The coefficients for 100, 200, and 300 MeV protons were obtained by using the Monte Carlo data of reference 4. The values at 400, 730, 1500, and 3000 MeV were obtained from the results of Alsmiller, Armstrong, and Coleman (ref. 8). The 10 GeV entry was obtained from the calculations of Armstrong and Chandler (ref. 9). The values that are footnoted in table 2 were obtained by interpolating between data points or smoothly extrapolating to unit buildup factors at proton energies near the Coulomb barrier for tissue nuclei ($\approx$12 MeV). The resulting buildup factors are shown in figures 1 and 2 and are compared with the Monte Carlo results; the error bars were determined by drawing smooth limiting curves to bracket the Monte Carlo values following the general functional dependence. These uncertainty limits should, therefore, be interpreted as limits of approximately two standard deviations, rather than the one standard deviation usually used in expressing uncertainty limits.

CONVERSION FACTOR COMPUTER CODE

To utilize equation (1) in a specific problem requires values for the conversion factor $R_n(z,E)$ over the range of interest. Formulas for these factors were presented in

the previous section. A computer code has been generated to return values of $R_n(z,E)$ for arbitrary depth z and energy E. This code is listed in the appendix and is described briefly here. There are six main functions to be generated relating to LET, range-energy relations, quality factor, and the functions relating to nuclear reaction effects given as nuclear survival probability and buildup factor.

The functions relating to ionization by the primary beam are generated by the function subroutine RTIS. Tables for r(E) and S(E) are generated on the first call to RTIS. Subsequent intermediate values are found by numerical interpolation above 10 KeV. A simplified approximation based on equation (4b) is used at lower energies. The function $\epsilon(z)$ is found by numerical inversion of r(E).

The quality factor is approximated by

$$Q_F(S) \approx 0.06S^{0.8}$$ (12)

for S greater than 35 MeV/cm and set to unity for smaller LET.

The values shown in table 1 for the optical thickness are generated in the function subroutine PN and stored in an array for numerical interpolation; the nuclear survival probability is calculated using equation (7).

The coefficients for calculating the buildup factors are generated by subroutine ANTER as a function of energy by interpolating between the values shown in table 2.

The conversion factors are generated by subroutine RESP by supplying parameters z and E, which represent distance in centimeters of tissue and proton energy in megaelectron volts; respectively. The returned values of the conversion factors have units of rads (or rems) per proton per centimeter squared.

SAMPLE CALCULATIONS

To illustrate the usage of the buildup factors described here, calculations of the dose in slab geometry for normal incident protons with spectra typical of the space environment have been made; calculations were also made neglecting nuclear reaction effects. The percentage contribution to the absorbed dose and dose equivalent due to nuclear reactions are shown in figures 3 and 4, respectively. The spectra indicated by GCR in the figures represent galactic cosmic radiation with the spectrum given by

$$\phi_{GCR}(E) = \phi_0\left(1 + \frac{E}{m_p}\right)^{-2.5}$$ (13)

The spectra denoted by the parameter p_0 represent solar cosmic ray spectra given as

$$\phi_{SCR}(E) = \phi_0 \exp\left[\frac{-p(E)}{p_0}\right] \tag{14}$$

with the rigidity given as

$$p(E) = \frac{1}{q}\left[E(E + 2m_p)\right]^{1/2} \tag{15}$$

where q is the proton charge and m_p is the proton mass. The value $p_0 = 100$ MV/c corresponds to an intermediate-energy solar event and $p_0 = 400$ MV/c corresponds to a high-energy solar event. The curve denoted by $E_0 = 100$ MeV represents the energetic inner belt protons with a spectrum

$$\phi(E) = \phi_0 \exp\left(\frac{-E}{E_0}\right) \tag{16}$$

It is clear from the figures that dose estimates for galactic cosmic rays and high-energy solar cosmic rays cannot be accurately calculated without proper account for nuclear reactions. This is especially true for estimates of the dose equivalent. Although reasonable estimates (±10 percent) of low and intermediate solar cosmic ray absorbed doses are expected, the dose equivalent estimates must include nuclear reaction effects. Marginally good estimates of absorbed dose for inner belt protons can be made by neglecting nuclear reactions, but dose equivalent estimates require inclusion of nuclear reaction effects.

CONCLUDING REMARKS

A set of computer subroutines have been developed to estimate dose and dose equivalent in tissue for incident protons, and the use of these subroutines in dose calculations in complex geometry has been discussed. It was found that numerically the effects of nuclear reactions generally cannot be neglected in the calculation of doses due to space proton irradiation.

Langley Research Center
National Aeronautics and Space Administration
Hampton, Va. 23665
May 3, 1976

APPENDIX

PROGRAM LISTING FOR CONVERSION FACTOR CALCULATION

The computer subroutines given in this appendix were developed for the present calculations, except for MGAUSS and IUNI which were taken from the mathematical subroutine library of the Langley Computer Complex.

APPENDIX

```
      SUBROUTINE RESP(EN,X,RAD,REM)

C     THIS SUBROUTINE GENERATES VALUES FOR THE SLAB CONVERSION FACTORS
C     FOR VALUES OF PROTON ENERGY EN (MEV) AND DEPTH IN THE SLAB X (CM)

      REAL C(8)
      ENER=EN
      EX=X
      CALL ANTER(ENER,C,R)
      RRES=R-EX
      ENERP=ETIS(RRES)
      IF(ENERP)34,33,34
33    CONTINUE
      RAD=0.
      REM=0.
      RETURN
34    CONTINUE
      CALL APROB(EX,ENER,PROB)
      CALL ATOPP(ENERP,STOPP)
   2  CALL AF(STOPP,QALF)
  22  PES=PROB*STOPP*QALF
      PRINT 1,C
      COREQ=(C(1)+X*(C(2)+X*C(3)))*EXP(-X*C(4))
      COREC=(C(5)+X*(C(6)+X*C(7)))*EXP(-X*C(8))
      IF(COREQ.LT.1.) COREQ=1.
      IF(COREC.LT.1.) COREC=1.
      PRINT 1,EN,X,ENERP,PROB,STOPP,QALF,COREQ,COREC
   1  FORMAT(2X,8F12.3)
      REM=PES*COREQ *1.6E-8
      PES=PROB*STOPP
      RAD=PES*COREC*1.6E-8
      RETURN
      END



      SUBROUTINE ANTER(ENER,C,R)

C     THIS SUBROUTINE GENERATES THE VALUES OF THE PARAMETERS
C     OF THE ANALYTIC FITS OF THE MONTE CARLO RESULTS

      REAL C(8),A(12,8),E(12)
      LOGICAL FALS
      DATA E/30.,60.,100.,150.,200.,300.,400.,730.,1200.,1500.,3000.,
     110000./
      DATA A/1.0,1.2,1.4,1.5,1.6,1.70,1.90,3.40,4.32,4.60,5.35,6.20,
     2 0.0,0.0,.02,.07,.09,.11,.13,.156,.167,.170,.190,.280,
     30.0,0.0,0.0,0.0,0.0,0.0,.00035,.00145,.0025,.0030,.0035,
     40.0,.013,.030,.0385,.040,.033,.0228,.0150,.013,.012,.010,.010,
     51.0,1.0,1.1,1.12,1.15,1.2,1.24,1.4,1.67,1.8,2.,2.3,
     60.0,.01,.040,.05,.062,.068,.071,.09,.094,.095,.10,.11,
     70.0,0.0,0.0,0.0,0.0,0.0,0.0,.0001,.00080,.0015,.002,.00205,
     80.0,.01,.026,.031,.032,.026,.0228,.015,.0122,.012,.01,.01/
      DATA FALS/.T./
      DATA IPT/-1/
      R=RTIS(ENER)
      IF(FALS) GO TO 10
   1  CONTINUE
      ELOG=ALOG(ENER)
      CALL IUNI(12,12,E,8,A,2,ELOG,C,IPT,IERR)
      RETURN
  10  CONTINUE
      DO 11 I=1,12
      E(I)=ALOG(E(I))
  11  CONTINUE
      FALS=.F.
      GO TO 1
      END
```

APPENDIX

```
      SUBROUTINE AF(STOPP,QALF)

C     THIS SUBROUTINE COMPUTES THE QUALITY FACTOR AS A FUNCTION OF
C     LINEAR ENERGY TRANSFER
      IF(STOPP-35.)11,11,12
   11 QALF=1.
      RETURN
   12 QALF=.06*STOPP**.8
      RETURN
      END



      SUBROUTINE APROB(EX,E,PROB)

C     THIS SUBROUTINE GENERATES VALUES FOR THE NUCLEAR SURVIVAL PROBABILITY
C     OF A PROTON OF ENERGY E (MEV) AFTER TRAVELING A DISTANCE EX (CM) IN TISSUE

      RRES=RTIS(E)-EX
      PROB=0.
      IF(RRES.LE.0.) RETURN
      ENEW=ETIS(RRES)
      PROB=PN(E)/PN(ENEW)
      RETURN
      END



      FUNCTION PN(E)

C     PN GIVES PROBABILITY THAT PROTON TRAVELS FULL RANGE WITHOUT
C     BEING ABSORBED

      EXTERNAL FOX
      LOGICAL TRU
      REAL R(30),ET(30)
      DATA ET/0.,10.,25.,50.,100.,150.,200.,250.,300.,350.,400.,500.,
     1700.,900.,1100.,1300.,1500.,1700.,2000.,2200.,2400.,2600.,2800.,
     23000.,4000.,5000.,6000.,7000.,8500.,10000./
      DATA TRU/.T./
      DATA IPT/-1/
      IF(TRU) GO TO 10
  111 ER=E
      CALL IUNI(30,30,ET,1,R,2,ER,BYRD,IPT,IERR)
      PN=EXP(-BYRD)
      RETURN
   10 TRU=.F.
      R(1)=0.
      DO 1 I=2,30
      EU=ET(I)
      G=ET(I-1)
      CALL MGAUSS(G,EU,04,ANS,FOX,F,1)
      R(I)=R(I-1)+ANS
    1 CONTINUE
      PRINT 19
   19 FORMAT(///,25X,*PN GRID*//)
      PRINT 119
  119 FORMAT (10X,*F VALUES FOR GRID*//)
      PRINT 226, ET
  226 FORMAT (2X,8E15.6)
      PRINT 227
  227 FORMAT (//,10X,*R VALUES FOR GRID*)
      PRINT 226,R
      GO TO 111
      END
```

12

APPENDIX

```
      SUBROUTINE FOX(X,F)

      ENER=X
    3 CALL ASIGM(ENER,SIGMA)
      CALL ATOPP(ENER,STOPP)
      F=SIGMA/STOPP
    2 RETURN
      END




      SUBROUTINE ASIGM(ENER,SIGMA)

C     THIS SUBROUTINE GENERATES VALUES OF TOTAL NONELASTIC MACROSCOPIC
C     CROSS SECTION (CM**2/G) IN TISSUE AS A FUNCTION OF PROTON ENERGY ENER(MEV)

      REAL EN(43),CROS(43)
      DATA EN/25.32,29.86,34.16,39.86,44.65,50.01,60.19,70.24,79.47,89.9
     11,100.8,117.9,139.3,156.3,175.3,186.6,202.2,266.1,304.7,375.2,407.
     27,471.6,507.1,574.5,611.4,678.3,714.5,776.4,809.3,870.4,916.8,1007
     3.,1129.,1406.,1786.,2024.,2318.,3071.,3428.,3943.,5000.,8000.,
     410000./
      DATA CROS/2.614,2.360,2.153,1.985,1.887,1.757,1.621,1.526,1.451,1.
     1379,1.327,1.261,1.211,1.187,1.164,1.152,1.141,1.097,1.087,1.100,1.
     2136,1.199,1.212,1.266,1.293,1.350,1.379,1.424,1.440,1.471,1.478,1.
     3504,1.477,1.480,1.483,1.485,1.487,1.475,1.461,1.463,1.46,1.458,
     41.452/
      DATA IPT/-1/
   11 E=ENER
      IF(ENER.LT.25.32) ENER=25.32
      CALL IUNI(43,43,EN,1,CROS,2,ENER,CROSS,IPT,IERR)
      SIGMA=(CROSS/100.)
      ENER=E
      RETURN
      END




      FUNCTION RTIS(E)

C     THIS SUBROUTINE GENERATES THE RANGE-ENERGY RELATIONS AND LET FOR
C     PROTONS IN TISSUE

      EXTERNAL ATOE
      REAL ET(57),RT(57),ST(57)
      LOGICAL FALSE
      DATA FALSE/.T./
      DATA NP/57/
      DATA ET/.01,.02,.03,.04,.05,.06,.07,.08,.09,.1,.2,.3,.4,.5,
     1.6,.7,.8,.9,1.,2.,3.,4.,5.,6.,7.,8.,9.,10.,20.,30.,40.,50.,
     260.,70.,80.,90.,100.,150.,200.,300.,400.,500.,600.,700.,
     3800.,900.,1000.,1500.,2000.,2500.,3000.,4000.,5000.,6000.,
     47000.,8500.,10000./
      N=1
      IF(FALSE) GO TO 10
   12 CONTINUE
      RTIS=E**.697/(2517.*.697)
      IF(E.LT..01) RETURN
      A=ALOG(E)
      DO 1 IE=2,NP
      IF(A.LT.ET(IE)) GO TO 2
    1 CONTINUE
    2 I=IE
      SLOPE=(RT(I)-RT(I-1))/(ET(I)-ET(I-1))
      RAL=RT(I-1)+SLOPE*(A-ET(I-1))
      RTIS=EXP(RAL)
      RETURN
      ENTRY STIS
```

```
      N=2
      IF(FALSE)GO TO 10
   13 CONTINUE
      RTIS=E**.303*(2517.-6283.*E)
      IF(E.LT..01) RETURN
      A=ALOG(E)
      DO 3 IE=2,NP
      IF(A.LT.ET(IE)) GO TO 4
    3 CONTINUE
    4 I=IE
      SLOPE=(ST(I)-ST(I-1))/(ET(I)-ET(I-1))
      SAL =ST(I-1)+SLOPE*(A-ET(I-1))
      RTIS=EXP(SAL)
      RETURN
      ENTRY ETIS
      N=3
      IF(FALSE)GO TO 10
   14 CONTINUE
      RTIS=(2517.*.697*E)**1.43472
      IF(E.LT..01) RETURN
      R=ALOG(E)
      DO 5 IR=2,NP
      IF(R.LT.RT(IR)) GO TO 6
    5 CONTINUE
    6 I=IR
      SLOPE=(ET(I)-ET(I-1))/(RT(I)-RT(I-1))
      EAL =ET(I-1)+SLOPE*(R-RT(I-1))
      RTIS=EXP(EAL)
      RETURN
   10 CONTINUE
      RT(1)=0.
      ST(1)=0.
      M=06
      DO 21 I=2,NP
      CALL ATOPP(ET(I),ST(I))
      CALL MGAUSS(ET(I-1),ET(I),M,ANS,ATOE,F,1)
   21 RT(I)=RT(I-1)+ANS
      RIRST=RT(2)
      EIRST=ET(2)
      DO 11  IX=2,NP
      ET(IX)=ALOG(ET(IX))
      RT(IX)=ALOG(RT(IX))
   11 ST(IX)=ALOG(ST(IX))
      FALSE=.F.
      GO TO (12,13,14)N
      END




      SUBROUTINE ATOE(E,F)

      CALL ATOPP(E,S)
       F=1./S
      RETURN
      END




      SUBROUTINE ATOPP(ENER,STOPP)

C     THIS SUBROUTINE COMPUTES THE STOPPING POWER FOR PROTON IN TISSUE

      IF(ENER.GT..2438) GO TO 2
      STOPP=(2517.-6283.*ENER)*ENER**.303
      RETURN
    2 ZETA=ENER/938.211
      BETAS=((ZETA*(ZETA+2.))/((ZETA+1.)**2))
      WBE=1.022201E6*BETAS/(1.-BETAS)
      FBET=ALOG(WBE)-BETAS
      STOPP=.30726148*(-2.2378342+.529726*FBET)/BETAS
      RETURN
      END
```

APPENDIX

```
      SUBROUTINE MGAUSS(A,B,N,SUM,FUNC,FOFX,NUMBER)


      DIMENSION U(5),R(5),SUM(1),FOFX(1)
      DO 1 LL=1,NUMBER
    1 SUM(LL)=0.0
      IF(A.EQ.B) RETURN
      U(1)=.425562830509184
      U(2)=.283302302935376
      U(3)=.160295215850488
      U(4)=.067468316655508
      U(5)=.013046735741414
      R(1)=.147762112357376
      R(2)=.13463335965499
      R(3)=.109543181257991
      R(4)=.074725674575290
      R(5)=.033335672154344
      FINE=N
      DELTA=FINE/(B-A)
      DO 3 K=1,N
      XI =K-1
      FINE=A+XI/DELTA
      DO 2 II=1,5
      UU=U(II)/DELTA+FINE
      CALL FUNC (UU,FOFX)
      DO 2 JOYBOY=1,NUMBER
    2 SUM(JOYBOY)=R(II)*FOFX(JOYBOY)+SUM(JOYBOY)
      DO 3 JJ=1,5
      UU=(1.0-U(JJ))/DELTA+FINE
      CALL FUNC (UU,FOFX)
      DO 3 NN=1,NUMBER
    3 SUM(NN)=R(JJ)*FOFX(NN)+SUM(NN)
      DO 7 IJK=1,NUMBER
    7 SUM(IJK)=SUM(IJK)/DELTA
      RETURN
      END
      SUBROUTINE IUNI(NMAX,N,X,NTAB,Y,IORDER,X0,Y0,IPT,IERR)          IUNI0010
C****************************************************************************IUNI0020
C*                                                                 *IUNI0030
C*      PURPOSE9                                                   *IUNI0040
C*                   SUBROUTINE IUNI USES FIRST OR SECOND ORDER    *IUNI0050
C*                   LAGRANGIAN INTERPOLATION TO ESTIMATE THE VALUES *IUNI0060
C*                   OF A SET OF FUNCTIONS AT A POINT X0.  IUNI     *IUNI0070
C*                   USES ONE INDEPENDENT VARIABLE TABLE AND A DEPENDENT *IUNI0080
C*                   VARIABLE TABLE FOR EACH FUNCTION TO BE EVALUATED. *IUNI0090
C*                   THE ROUTINE ACCEPTS THE INDEPENDENT VARIABLES SPACED *IUNI0100
C*                   AT EQUAL OR UNEQUAL INTERVALS.  EACH DEPENDENT *IUNI0110
C*                   VARIABLE TABLE MUST CONTAIN FUNCTION VALUES CORRES- *IUNI0120
C*                   PONDING TO EACH X(I) IN THE INDEPENDENT VARIABLE *IUNI0130
C*                   TABLE.  THE ESTIMATED VALUES ARE RETURNED IN THE YO *IUNI0140
C*                   ARRAY WITH THE N-TH VALUE OF THE ARRAY HOLDING THE *IUNI0150
C*                   VALUE OF THE N-TH FUNCTION VALUE EVALUATED AT X0. *IUNI0160
C*                                                                 *IUNI0170
C*      USE9                                                       *IUNI0180
C*                   CALL IUNI(NMAX,N,X,NTAB,Y,IORDER,X0,YO,IPT,IERR) *IUNI0190
C*                                                                 *IUNI0200
C* PARAMETERS9                                                     *IUNI0210
C*                                                                 *IUNI0220
C*      NMAX    THE MAXIMUM NUMBER OF POINTS IN THE INDEPENDENT     *IUNI0230
C*              VARIABLE ARRAY.                                    *IUNI0240
C*                                                                 *IUNI0250
C*       N      THE ACTUAL NUMBER OF POINTS IN THE INDEPENDENT      *IUNI0260
C*              ARRAY,WHERE N .LE. NMAX.                           *IUNI0270
C*                                                                 *IUNI0280
C*       X      A ONE-DIMENSIONAL ARRAY, DIMENSIONED (NMAX) IN THE  *IUNI0290
C*              CALLING PROGRAM, WHICH CONTAINS THE INDEPENDENT     *IUNI0300
C*              VARIABLES.  THESE VALUES MUST BE STRICTLY MONOTONIC. *IUNI0310
C*                                                                 *IUNI0320
C*      NTAB    THE NUMBER OF DEPENDENT VARIABLE TABLES            *IUNI0330
C*                                                                 *IUNI0340
C*       Y      A TWO-DIMENSIONAL ARRAY DIMENSIONED (NMAX,NTAB) IN  *IUNI0350
C*              THE CALLING PROGRAM.  EACH COLUMN OF THE ARRAY      *IUNI0360
C*              CONTAINS A DEPENDENT VARIABLE TABLE                *IUNI0370
C*                                                                 *IUNI0380
```

```
C*       IORDER      INTERPOLATION PARAMETER SUPPLIED BY THE USER.         *IUNI0390
C*                                                                        *IUNI0400
C*                   =0   ZERO ORDER INTERPOLATION9 THE FIRST FUNCTION     *IUNI0410
C*                        VALUE IN EACH DEPENDENT VARIABLE TABLE IS        *IUNI0420
C*                        ASSIGNED TO THE CORRESPONDING MEMBER OF THE YO   *IUNI0430
C*                        ARRAY.  THE FUNCTIONAL VALUE IS ESTIMATED TO     *IUNI0440
C*                        REMAIN CONSTANT AND EQUAL TO THE NEAREST KNOWN   *IUNI0450
C*                        FUNCTION VALUE.                                  *IUNI0460
C*                                                                        *IUNI0470
C*       XO          THE INPUT POINT AT WHICH INTERPOLATION WILL BE        *IUNI0480
C*                   PERFORMED.                                            *IUNI0490
C*                                                                        *IUNI0500
C*       YO          A ONE-DIMENSIONAL ARRAY DIMENSIONED (NTAB) IN THE     *IUNI0510
C*                   CALLING PEOGRAM.  UPON RETURN THE ARRAY CONTAINS THE  *IUNI0520
C*                   ESTIMATED VALUE OF EACH FUNCTION AT XO.               *IUNI0530
C*                                                                        *IUNI0540
C*       IPT         ON THE FIRST CALL IPT MUST BE INITIALIZED TO -1 SO    *IUNI0550
C*                   THAT MONOTONICITY WILL BE CHECKED. UPON LEAVING THE   *IUNI0560
C*                   ROUTINE IPT EQUALS THE VALUE OF THE INDEX OF THE X    *IUNI0570
C*                   VALUE PRECEDING XO UNLESS EXTRAPOLATION WAS           *IUNI0580
C*                   PERFORMED.  IN THAT CASE THE VALUE OF IPT IS          *IUNI0590
C*                   RETURNED AS9                                          *IUNI0600
C*                   =0   DENOTES XO .LT. X(1) IF THE X ARRAY IS IN        *IUNI0610
C*                        INCREASING ORDER AND X(1) .GT. XO IF THE X ARRAY *IUNI0620
C*                        IS IN DECREASING ORDER.                          *IUNI0630
C*                   =N   DENOTES XO .GT. X(N) IF THE X ARRAY IS IN        *IUNI0640
C*                        INCREASING ORDER AND XO .LT. X(N) IF THE X ARRAY *IUNI0650
C*                        IS IN DECREASING ORDER.                          *IUNI0660
C*                                                                        *IUNI0670
C*                   ON SUBSEQUENT CALLS. IPT IS USED AS A POINTER TO      *IUNI0680
C*                   BEGIN THE SEARCH FOR XO.                              *IUNI0690
C*                                                                        *IUNI0700
C*       IERR        ERROR PARAMETER GENERATED BY THE ROUTINE              *IUNI0710
C*                   =0   NORMAL RETURN                                    *IUNI0720
C*                   =J   THE J-TH ELEMENT OF THE X ARRAY IS OUT OF ORDER  *IUNI0730
C*                   =-1  ZERO ORDER INTERPOLATION PERFORMED BECAUSE       *IUNI0740
C*                        IORDER =0.                                       *IUNI0750
C*                   =-2  ZERO ORDER INTERPOLATION PERFORMED BECAUSE ONLY  *IUNI0760
C*                        ONE POINT WAS IN X ARRAY.                        *IUNI0770
C*                   =-3. NO INTERPOLATION WAS PERFORMED BECAUSE           *IUNI0780
C*                        INSUFFICIENT POINTS WERE SUPPLIED FOR SECOND     *IUNI0790
C*                        ORDER INTERPOLATION.                             *IUNI0800
C*                   =-4  EXTRAPOLATION WAS PERFORMED                      *IUNI0810
C*                                                                        *IUNI0820
C*                   UPON RETURN THE PARAMETER IERR SHOULD BE TESTED IN    *IUNI0830
C*                   THE CALLING PROGRAM.                                  *IUNI0840
C*                                                                        *IUNI0850
C*    REQUIRED ROUTINES                    NONE                            *IUNI0860
C*                                                                        *IUNI0870
C*    SOURCE                               CMPB ROUTINE MTLUP MODIFIED     *IUNI0880
C*                                         BY COMPUTER SCIENCES CORPORATION*IUNI0890
C*                                                                        *IUNI0900
C*    LANGUAGE                             FORTRAN                         *IUNI0910
C*                                                                        *IUNI0920
C*                                                                        *IUNI0930
C*    DATE RELEASED                        AUGUST 1,1973                   *IUNI0940
C*                                                                        *IUNI0950
C*    LATEST REVISION                      JUNE 9, 1975                    *IUNI0960
C*                                                                        *IUNI0970
C***************************************************************************IUNI0980
      DIMENSION X(1),Y(NMAX,1),YO(1)                                       IUNI0990
      NM1=N-1                                                              IUNI1000
      IERR=0                                                              IUNI1010
      J=1                                                                 IUNI1020
C                                                                         IUNI1030
C             TEST FOR ZERO ORDER INTERPOLATION                           IUNI1040
C                                                                         IUNI1050
      DELX=X(2)-X(1)                                                      IUNI1060
      IF (IORDER .EQ. 0) GO TO 10                                         IUNI1070
      IF (N.LT. 2) GO TO 20                                               IUNI1080
      GO TO 50                                                            IUNI1090
```

```
      10    IERR=-1                                                      IUNI1100
            GO TO 30                                                     IUNI1110
      20    IERR=-2                                                      IUNI1120
      30    DO 40 NT=1,NTAB                                              IUNI1130
               YO(NT)=Y(1,NT)                                           IUNI1140
      40       CONTINUE                                                 IUNI1150
            RETURN                                                      IUNI1160
      50    IF (IPT .GT. -1) GO TO 65                                   IUNI1170
C                                                                       IUNI1180
C             CHECK FOR TABLE OF NODE POINTS BEING STRICTLY MONOTONIC   IUNI1190
C             THE SIGN OF DELX SIGNIFIES WHETHER TABLE IS IN            IUNI1200
C             INCREASING OR DECREASING ORDER.                          IUNI1210
C                                                                       IUNI1220
            IF (DELX .EQ. 0) GO TO 190                                  IUNI1230
            IF (N .EQ. 2) GO TO 65                                      IUNI1240
C                                                                       IUNI1250
C             CHECK FOR SIGN CONSISTENCY IN THE DIFFERENCES OF          IUNI1260
C             SUBSEQUENT PAIRS                                          IUNI1270
C                                                                       IUNI1280
            DO 60 J=2,NM1                                               IUNI1290
               IF (DELX * (X(J+1)-X(J))) 190,190,60                     IUNI1300
      60       CONTINUE                                                 IUNI1310
C                                                                       IUNI1320
C             IPT IS INITIALIZED TO BE WITHIN THE INTERVAL              IUNI1330
C                                                                       IUNI1340
      65    IF (IPT .LT. 1) IPT=1                                       IUNI1350
            IF (IPT .GT. NM1) IPT=NM1                                   IUNI1360
            IN= SIGN (1.0,DELX *( X0-X(IPT)))                           IUNI1370
      70    P= X(IPT) - X0                                              IUNI1380
            IF (P* (X(IPT +1)- X0)) 90,180,80                           IUNI1390
      80    IPT =IPT +IN                                                IUNI1400
C                                                                       IUNI1410
C             TEST TO SEE IF IT IS NECCESARY TO EXTRAPOLATE             IUNI1420
C                                                                       IUNI1430
            IF (IPT.GT.0 .AND. IPT .LT. N) GO TO 70                     IUNI1440
            IERR=-4                                                     IUNI1450
            IPT=IPT- IN                                                 IUNI1460
C                                                                       IUNI1470
C             TEST FOR ORDER OF INTERPOLATION                           IUNI1480
C                                                                       IUNI1490
C                                                                       IUNI1500
      90    IF (IORDER .GT. 1) GO TO 120                                IUNI1510
C                                                                       IUNI1520
C             FIRST ORDER INTERPOLATION                                 IUNI1530
C                                                                       IUNI1540
            IPT1=IPT+1                                                  IUNI1550
            XTMP1=X0-X(IPT)                                            IUNI1560
            XTMP2=X(IPT1)-X(IPT)                                       IUNI1570
            XTMP1=XTMP1/XTMP2                                          IUNI1580
            DO 100 NT=1,NTAB                                            IUNI1590
               YTMP=Y(IPT1,NT)-Y(IPT,NT)                               IUNI1600
               YO(NT)=Y(IPT,NT)+YTMP*XTMP1                             IUNI1610
      100      CONTINUE                                                 IUNI1620
            IF (IERR .EQ. -4) IPT=IPT+IN                                IUNI1630
            RETURN                                                      IUNI1640
C                                                                       IUNI1650
C             SECOND ORDER INTERPOLATION                                IUNI1660
C                                                                       IUNI1670
      120   IF (N .EQ. 2) GO TO 200                                     IUNI1680
C                                                                       IUNI1690
C             CHOOSING A THIRD POINT SO AS TO MINIMIZE THE DISTANCE     IUNI1700
C             BETWEEN THE THREE POINTS USED TO INTERPOLATE              IUNI1710
C                                                                       IUNI1720
            IF (IPT .EQ. NM1) GO TO  140                                IUNI1730
            IF (IPT .EQ. 1) GO TO 130                                   IUNI1740
            A1=ABS(X0-X(IPT-1))                                        IUNI1750
            A2=ABS(X(IPT+2)-X0)                                        IUNI1760
            IF(A1-A2)140,130,130                                       IUNI1770
      130   L=IPT                                                       IUNI1780
            GO TO 150                                                   IUNI1790
      140   L=IPT -1                                                    IUNI1800
      150   V1=X(L)-X0                                                  IUNI1810
```

```
         V2=X(L+1)-X0                                                 IUNI1820
         V3=X(L+2)-X0                                                 IUNI1830
         DO 160 NT=1,NTAB                                             IUNI1840
         YY1=(Y(L,NT) * V2 - Y(L+1,NT) * V1)/(X(L+1) - X(L))          IUNI1850
         YY2=(Y(L+1,NT)*V3-Y(L+2,NT) *V2)/(X(L+2)-X(L+1))             IUNI1860
         YO(NT)=(YY1*V3-YY2*V1)/(X(L+2)-X(L))                         IUNI1870
  160 CONTINUE                                                        IUNI1880
      IF (IERR .EQ. -4) IPT=IPT + IN                                  IUNI1890
      RETURN                                                          IUNI1900
  180 IF(P .NE. 0) IPT=IPT +1                                         IUNI1910
      DO 185 NT=1,NTAB                                                IUNI1920
         YO(NT)=Y(IPT,NT)                                             IUNI1930
  185     CONTINUE                                                    IUNI1940
      RETURN                                                          IUNI1950
C                                                                     IUNI1960
C        .      IERR IS SET TO THE SUBSCRIPT OF THE MEMBER OF THE TABLE IUNI1970
C              WHICH IS OUT OF ORDER                                  IUNI1980
C                                                                     IUNI1990
  190 IERR=J +1                                                       IUNI2000
      RETURN                                                          IUNI2010
  200 IERR=-3                                                         IUNI2020
      RETURN                                                          IUNI2030
      END                                                             IUNI2040
```

REFERENCES

1. Alsmiller, R. G., Jr.: High-Energy Nucleon Transport and Space Vehicle Shielding. Nucl. Sci. & Eng., vol. 27, no. 2, Feb. 1967, pp. 158-189.

2. Wilson, John W.; and Khandelwal, G. S.: Proton Dose Approximation in Arbitrary Convex Geometry. Nucl. Technol., vol. 23, no. 3, Sept. 1974, pp. 298-305.

3. Neufeld, Jacob; and Wright, Harvel: Radiation Levels and Fluence Conversion Factors. Health Phys., vol. 23, no. 2, Aug. 1972, pp. 183-186.

4. Turner, J. E.; Zerby, C. D.; Woodyard, R. L.; Wright, H. A.; Kinney, W. E.; Snyder, W. S.; and Neufeld, J.: Calculation of Radiation Dose From Protons to 400 MeV. Health Phys., vol. 10, no. 11, Nov. 1974, pp. 783-808.

5. Zerby, C. D.; and Kinney, W. E.: Calculated Tissue Current-to-Dose Conversion Factors for Nucleons Below 400 MeV. Nucl. Instrum. & Methods, vol. 36, no. 1, Sept. 1965, pp. 125-140.

6. Snyder, W. S.; Wright, H. A.; Turner, J. E.; and Neufeld, Jacob: Calculations of Depth-Dose Curves for High-Energy Neutrons and Protons and Their Interpretation for Radiation Protection. Nucl. Appl., vol. 6, no. 4, Apr. 1969, pp. 336-343.

7. Wright, Harvel A.; Anderson, V. E.; Turner, J. E.; Neufeld, Jacob; and Snyder, W. S.: Calculation of Radiation Dose Due to Protons and Neutrons With Energies From 0.4 to 2.4 GeV. Health Phys., vol. 16, no. 1, Jan. 1969, pp. 13-31.

8. Alsmiller, R. G., Jr.; Armstrong, T. W.; and Coleman, W. A.: The Absorbed Dose and Dose Equivalent From Neutrons in the Energy Range 60 to 3000 MeV and Protons in the Energy Range 400 to 3000 MeV. Nucl. Sci. & Eng., vol. 42, no. 3, Dec. 1970, pp. 367-381.

9. Armstrong, T. W.; and Chandler, K. C.: Calculation of the Absorbed Dose and Dose Equivalent From Neutrons and Protons in the Energy Range From 3.5 GeV to 1.0 TeV. ORNL-TM-3758, U.S. At. Energy Comm., May 1970.

10. Armstrong, T. W.; and Bishop, B. L.: Calculation of the Absorbed Dose and Dose Equivalent Induced by Medium-Energy Neutrons and Protons and Comparison With Experiment. Radiat. Res., vol. 47, no. 3, Sept. 1971, pp. 581-588.

11. Wright, H. A.; Hamm, R. N.; and Turner, J. E.: Effect of Lateral Scattering on Absorbed Dose From 400 MeV Neutrons and Protons. International Congress on Protection Against Accelerator and Space Radiation, J. Baarli and J. Dutrannois, eds., CERN 71-16, Vol. 1, European Organ. Nucl. Res., July 1, 1971, pp. 207-219.

12. Bertini, Hugo W.: Low-Energy Intranuclear Cascade Calculation. Phys. Rev., Second ser., vol. 131, no. 4, Aug. 15, 1963, pp. 1801-1821.

13. Bertini, Hugo W.: Intranuclear-Cascade Calculation of the Secondary Nucleon Spectra From Nucleon-Nucleus Interactions in the Energy Range 340 to 2900 MeV and Comparisons With Experiment. Phys. Rev., Second ser., vol. 188, no. 4, Dec. 20, 1969, pp. 1711-1930.

14. Bertini, Hugo W.; and Guthrie, Miriam P.: News Items — Results From Medium-Energy Intranuclear-Cascade Calculations. Nucl. Phys., vol. A169, no. 3, July 1971, pp. 670-672.

15. Report of Committee IV on Protection Against Electromagnetic Radiation Above 3 MeV and Electrons, Neutrons and Protons. ICRP Publ. 4, The Macmillan Co., 1964.

16. Schaefer, Hermann J.; and Sullivan, Jeremiah J.: Nuclear Emulsion Recordings of the Astronauts' Radiation Exposure on the First Lunar Landing Mission Apollo XI. NAMRL-1112, U.S. Navy, June 29, 1970. (Available as NASA CR-115804.)

17. Alsmiller, R. G., Jr.; Santoro, R. T.; Barish, J.; and Claiborne, H. C.: Shielding of Manned Space Vehicles Against Protons and Alpha Particles. ORNL-RSIC-35, U.S. At. Energy Comm., Nov. 1972.

TABLE 1.- TOTAL TISSUE OPTICAL THICKNESS

FOR PROTONS

E, GeV	$\tau(E)$	E, GeV	$\tau(E)$
0	0	1.3	6.57
.01	.0033	1.5	8.03
.025	.0171	1.7	9.52
.05	.0510	2.0	11.76
.1	.135	2.2	13.27
.15	.239	2.4	14.78
.2	.362	2.6	16.29
.25	.501	2.8	17.79
.3	.655	3.0	19.29
.35	.822	4.0	26.62
.4	1.004	5.0	33.81
.5	1.429	6.0	40.84
.7	2.471	7.0	47.75
.9	3.743	8.5	57.91
1.1	5.143	10.0	67.85

TABLE 2.- BUILDUP-FACTOR PARAMETERS

E, GeV	Buildup-factor parameters for dose equivalent				Buildup-factor parameters for absorbed dose			
	a_1	a_2	a_3	a_4	a_1	a_2	a_3	a_4
0.03	*1.00	*0	*0	*0	*1.00	*0	*0	*0
.06	*1.20	*0	*0	*.0130	*1.07	*.010	*0	*.010
.10	1.40	.020	0	.0300	1.10	.040	0	.026
.15	*1.50	*.070	*0	*.0385	*1.12	*.060	*0	*.031
.20	1.60	.090	0	.0400	1.15	.062	0	.032
.30	1.70	.110	0	.0330	1.20	.068	0	.026
.40	1.90	.130	0	.0228	1.24	.071	0	.0228
.73	3.40	.156	.00035	.0150	1.40	.090	.0001	.0150
1.2	*4.32	*.167	*.00145	*.0130	*1.67	*.094	*.0008	*.0122
1.5	4.60	.170	.00250	.0120	1.80	.095	.0015	.0120
3.0	5.35	.190	.00300	.0100	2.00	.100	.0020	.0100
10.0	6.20	.280	.00350	.0100	2.30	.111	.00205	.0100

*Values obtained by interpolation.

Figure 1.- Buildup factors for absorbed dose for several depths in tissue as a function of incident proton energy.


Figure 2.- Buildup factors for dose equivalent for several depths in tissue as a function of incident proton energy.

23

Figure 3.- Contribution of nuclear reactions to absorbed dose of the common space radiations.


Figure 4.- Contribution of nuclear reactions to dose equivalent of common space radiations.

"The aeronautical and space activities of the United States shall be conducted so as to contribute . . . to the expansion of human knowledge of phenomena in the atmosphere and space. The Administration shall provide for the widest practicable and appropriate dissemination of information concerning its activities and the results thereof."
—NATIONAL AERONAUTICS AND SPACE ACT OF 1958

NASA SCIENTIFIC AND TECHNICAL PUBLICATIONS

TECHNICAL REPORTS: Scientific and technical information considered important, complete, and a lasting contribution to existing knowledge.

TECHNICAL NOTES: Information less broad in scope but nevertheless of importance as a contribution to existing knowledge.

TECHNICAL MEMORANDUMS: Information receiving limited distribution because of preliminary data, security classification, or other reasons. Also includes conference proceedings with either limited or unlimited distribution.

CONTRACTOR REPORTS: Scientific and technical information generated under a NASA contract or grant and considered an important contribution to existing knowledge.

TECHNICAL TRANSLATIONS: Information published in a foreign language considered to merit NASA distribution in English.

SPECIAL PUBLICATIONS: Information derived from or of value to NASA activities. Publications include final reports of major projects, monographs, data compilations, handbooks, sourcebooks, and special bibliographies.

TECHNOLOGY UTILIZATION PUBLICATIONS: Information on technology used by NASA that may be of particular interest in commercial and other non-aerospace applications. Publications include Tech Briefs, Technology Utilization Reports and Technology Surveys.

Details on the availability of these publications may be obtained from:

SCIENTIFIC AND TECHNICAL INFORMATION OFFICE

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION
Washington, D.C. 20546